



RAYDOOR®
Sliding Walls & Doors

----- **CLEANING INFORMATION** -----

FRAME CARE INSTRUCTIONS

Many glass or general-purpose surface cleaners are safe to use when cleaning or wiping down the frames. However, they are not to be used on the acrylic.

ACRYLIC CARE INSTRUCTIONS

DUSTING

Dust with a soft, damp cloth or chamois. Dry or gritty cloths may cause surface scratches and create a static electric charge on the surface.

WASHING PANELS

STEP 1: soak a clean soft cloth in HOT water; ring it out well so that it doesn't drip. Then wipe down the acrylic in a circular motion applying only light pressure. Once the cloth becomes warm, repeat step 1 until the entire door has been wiped down.

STEP 2: dry completely by blotting with a damp cloth or chamois. If, stains persist, try step 1 again with a solution of mild soap or detergent. Grease, oil or tar maybe removed with a good grade of hexane, aliphatic naphtha, or kerosene. These solvents may be obtained at a paint or hardware store and should be used in accordance with manufacturers recommendations.

DO NOT USE: Window cleaning sprays, kitchen scouring compounds, or solvents such as acetone, gasoline, benzene, alcohol, carbon tetrachloride or lacquer thinner. These can scratch the acrylics surface and/or weaken it causing small surface cracks.

CLEANING MATERIAL SUPPLIERS:

20/20Plasti-Cleaner Craftics, Inc.
2701 N. Pulaski Chicago, IL 60639
800.289.2020

Anstac 2M Cleaner Chemical Development Corporation
22 Portsmouth Road Ames Bury, MA 01913
708.547.6650

210 & 210 Plus Plastic Cleaner Sumner Laboratories
210 Lincoln Street Boston, MA 02111
617.542.8656